



Pentra® -Sil

(NL) Hardener, Densifier

Convergent Group S.A.

Specialty Chemical Concrete
Treatments Commercial

Products Group
Zoning Industriel de Mariembourg
Rue des Mousquetaires Gris, 35
B-5660 Mariembourg
Belgium - Europe
Office: +32 60 390 752
Fax: +32 60 390 751

www.convergent-group.com



nanoLithium
Patented Technologies by Advan
Nano-Lithium® (NL)
Concrete Treatment
www.nano-lithium.com



PRODUCT DESCRIPTION

Pentra®-Sil (NL) is a premium lithium polysilicate performance densifier for concrete surfaces. This high solids formula provides maximum hardening to improve abrasion resistance and reduce dusting. This easy-to-use water-based solution requires no rinsing and is VOC compliant in all areas of the world. When sprayed on new or existing concrete, it penetrates up to 7mm where it reacts with free calcium to form insoluble calcium silica hydrate, which makes concrete more water, stain, and abrasion resistant for easier maintenance and longer life. It is also suitable for concrete polishing procedures and helps prolong the life of polished finishes.

KEY BENEFITS:

- Easy application, no rinsing required
- Penetrates, no film to lift or peel off
- Reduces efflorescence and surface sweating
- Does not contribute to surface ASR or promote crazing
- VOC Compliant, can contribute to LEED points (IEQ credit 4.2 non-emitting materials)
- Prolongs finish of polished surfaces
- Resists stains and dusting, making concrete and facilities easier to maintain

USES

NEW AND EXISTING CONCRETE

Manufacturing, Warehousing, Storage, Distribution centers, Food processing plants, Textile mills, Wastewater treatment plants, Pharmaceutical, Electronic facilities, Cold Storage/Freezers, Beverage bottling, Chemical processing, Parking garages, Aircraft hangars, Automotive dealerships, Shipping terminals, Vehicle maintenance areas, Office buildings, Health care facilities, Cafeterias/restaurants, Correctional institutions, Retail & shopping centers, Schools, Stadiums, Veterinary clinics, Common Areas, Aisles/corridors, Clean rooms, Kitchens, Laboratories, Loading docks, Lobbies, Mechanical rooms, Mezzanines, Restrooms & showers.

CUSTOMER SERVICE:

(+32 60 390 752) to verify the most current versions, visit our website: www.convergent-group.com or scan the code.

**APPLICATION**

BEFORE APPLICATION, ALWAYS DO A SMALL TEST SAMPLE IN A LESS-VISIBLE AREA TO BE SURE THERE ARE NO VARIABLES OR CONTAMINANTS IN THE SUBSTRATE THAT MAY BE INCOMPATIBLE WITH THIS PRODUCT.

Precautions: Apply only when temperatures will be above 2°C for at least 4 hours following application. Clean surface to remove any dirt, laitance, curing compounds or coatings that may prevent **Pentra®-Sil (NL)** from penetrating the surface. Do not use citrus or acidic cleaners. If acid dyes or cleaners have been used, neutralize the surface using an alkali cleaner (TSP, Tide laundry detergent, etc.). Do not use high pressure sprayers. In hot, windy conditions, it may be necessary to spray water on hot concrete to cool the surface prior to application so **Pentra®-Sil (NL)** does not flash-dry on the surface. If **Pentra®-Sil (NL)** comes into contact with glass, fabric, metal, or painted surfaces, immediately wipe contaminated surfaces with a damp cloth, then wipe dry with a second clean cloth. Using an HVLP sprayer, or a pump-up sprayer for smaller jobs, spray **Pentra®-Sil (NL)** evenly on the surface. Spread out any pools with a soft bristle broom or a flat microfiber pad. Keep surface wet for at least 20 minutes, adding more material where needed. Surface is ready for use when dry, but the complete reaction may take up to two weeks to develop depending on site temperature and conditions.

In cool, humid, or enclosed conditions, Pentra®-Sil (NL) may stay wet for a long time. After 1 hour of dwell time, use an auto-scrubber to rinse the surface and pick up excess material.

If concrete is dyed, acid stained, or integrally colored, after 20-30 minutes of dwell time, use scrubbing equipment to rinse the surface and pick up excess material. After bringing the surface to the desired surface profile by grinding or buffing, **Pentra®-Finish (HG)** may be applied to enhance gloss, stain, and wear protection.

Interior: On newly placed interior machine-troweled concrete, **Pentra®-Sil (NL)** may be applied immediately after the finishing, or immediately after joints have been cut and cleaned, or anytime thereafter, at the project manager's discretion. If at time-of-placement, curing materials/bond breakers may be applied over the top of **Pentra®-Sil (NL)** once it is no longer wet on the surface/dry to the touch.

Exterior: On exterior concrete that has not been machine-troweled, wait until the surface is hard enough to bear foot traffic without damage before applying **Pentra®-Sil (NL)**. If conditions are such that the project manager deems it necessary to apply curing materials before the surface is hard enough to bear foot traffic, it may be necessary to apply **Pentra®-Sil (NL)** at a later time after removing the curing material.

ESTIMATED COVERAGE

Steel Troweled Finish: 1 liter per 12 to 19m². Coverage rate will vary with concrete finish and porosity—broom finished concrete will require more material.

CLEAN UP

Use soap and water to clean tools and equipment. Although **Pentra®-Sil (NL)** is non-toxic and environmentally safe, it is alkaline—use up or dry out extra material and dispose of according to local regulations. Don't pour into sewer systems or storm drains.

SAFETY/HEALTH INFORMATION

KEEP OUT OF REACH OF CHILDREN. This product is alkali. Do not drink. If swallowed, do not induce vomiting, drink 2 glasses of water and call physician. Keep container closed tightly when not in use. Wear goggles and gloves. If splashed in eyes, rinse eyes immediately with clean water and call a physician if irritation persists. **Pentra®-Sil (NL)** will dry out and irritate the skin. Clean skin with soap and water promptly. **CAUTION:** Surfaces wet with **Pentra®-Sil (NL)** may be slippery. Additional precautions, safety information and first aid treatments are contained in the Material Safety Data Sheet.

PROPERTIES

Active Ingredients:	100% of total solids
Specific Gravity:	1.11
Wt/liter:	1 kg
pH:	11
VOC Content:	<50g/L
Flash Point:	N/A
Freeze Point:	0°C
Shelf Life:	2 Years in unopened factory sealed container

PACKAGING

20 L Basket

200 L Drum

600 L Tote

1000 L Tote

LIMITATIONS

Pentra®-Sil (NL) will not bridge or fill cracks and will not salvage honeycombed or structurally unsound surfaces. Not suitable for asphalt, non-cement surfaces or painted surfaces. (Paint and coatings may be applied over the top of **Pentra®-Sil (NL)**—follow paint or coating manufacturer's instructions)

TECHNICAL SERVICE

Customer Care
+32 60 390 752

EMAIL

technical@convergent-group.com

WEB

www.convergent-group.com

For chemical/medical emergencies only,

Anti Poison BE +32 70 245 245
Outside USA 352-323-3500

WARRANTY

LIMITED WARRANTY NOTICE. Every reasonable effort is made to apply exacting standards both in the manufacture of our products and in the information that we issue concerning these products and their use. We warrant our products to be of good quality and will replace or, at our election, refund the purchase price of any products proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement or refund, CONVERGENT GROUP S.A. ("CONVERGENT") MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY, RESPECTING ITS PRODUCTS, and CONVERGENT shall have no other liability with respect thereto. Any claim regarding product defect must be received in writing within one (1) year from the date of shipment. No claim will be considered without such written notice or after the specified time interval. User shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith. Any authorized change in the printed recommendations concerning the use of our products must bear the signature of CONVERGENT'S Research Director. This information and all further technical advice are based on CONVERGENT'S present knowledge and experience. However, CONVERGENT assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights. In particular, CONVERGENT disclaims all WARRANTIES, WHETHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. CONVERGENT SHALL NOT BE RESPONSIBLE FOR CONSEQUENTIAL INDIRECT OR INCIDENTAL DAMAGES (INCLUDING LOSS OF PROFITS) OF ANY KIND. CONVERGENT reserves the right to make any changes according to technological progress or further developments. It is the customer's (Authorized Applicator) responsibility and obligation to carefully inspect and test any incoming goods. Performance of the product(s) described herein should be verified by testing and carried out only by qualified experts. It is the sole responsibility of the customer to carry out and arrange for any such testing. Reference to trade names used by other companies is neither a recommendation, nor an endorsement of any product and does not imply that similar products could not be used. CONVERGENT reserves the right to change specifications referred to in this literature at any time, without prior notice. The information contained herein is, to our knowledge, true and accurate. While this material is furnished in good faith, no warranty expressed or implied, of merchantability, completeness, fitness or otherwise is made. This material is offered only for your consideration, investigation and verification, and CONVERGENT disclaims any liability incurred from the use thereof and shall not in any event, be liable for any special, incidental or consequential damages arising from such use. This information is not intended to be all inclusive and the manner and conditions of use and handling of any material may involve other or additional considerations specific to the use or user. Nothing herein should be construed as permission or recommendation to infringe any patent or as to any specific use. No agent, representative or employee of this company is authorized to vary any term of this notice.



CONVERGENT GROUP

CONCRETE TECHNOLOGIES

Refer to www.convergent-group.com for latest Technical Data Sheet and MSDS.

Convergent Group S.A. - Specialty Chemical Concrete Treatments * ZI de Mariembourg * Rue des Mousquetaires Gris, 35 * 5660 Mariembourg
* Belgique (Europe) * +32 60 390 752

UNIQUE STRENGTHS, UNMATCHED PERFORMANCE.™

©2020 Convergent Group S.A. All Rights Reserved.

Pentra®-Sil (NL) is a registered trademark of Convergent Group S.A. Nano-Lithium® brand name and logo are registered trademarks of Advanced Concrete Technologies, LLC ("ADVAN") and sub-licensed to Convergent Group S.A., under a non exclusive co-brand/technology license. All rights reserved. Products manufactured and marketed by CONVERGENT GROUP S.A. are protected by patents and/or pending patents under license in the United States and other countries by ADVANCED CONCRETE TECHNOLOGIES, LLC. ADVANCED CONCRETE TECHNOLOGIES, LLC makes no claim as to the product performance or product shown to be other than as warranted. REVISION DATE010220