



Convergent Group S.A.

Specialty Chemical Concrete Treatments Commercial

Products Group Zoning Industriel de Mariembourg Rue des Mousquetaires Gris, 35 B-5660 Mariembourg Belgium - Europe Office: +32 60 390 752 Fax: +32 60 390 751

www.convergent-group.com



Patented Technologies by Advan

Nano-Lithium® (NL) Concrete Treatment www.nano-lithium.com





PRODUCT DESCRIPTION

Pentra®-Sil (C&N) cleans and neutralizes concrete that suffers from efflorescence, sweating, and other alkalinity problems. Pentra®-Sil (C&N) Lithium fixer for Concrete Efflorescence and Sweating Problems works by infusing lithium ions into the substrate—these ions calm alkali reactions between aggregate and

Portland cement thereby reducing the formation of alkali salts and sweating. (For serious problems we recommend a full treatment of **Pentra®-Sil (C&N)**, **Pentra®-Sil (AC)**, and **Pentra®-Sil (HD)**). **Pentra®-Sil (C&N)** is also excellent for cleaning concrete after diamond polishing. **Pentra®-Sil (C&N)** removes fine particles and dust that can reduce shine.

KEY BENEFITS

- Stabilizes and fortifies concrete surfaces by infusing lithium ions into the substrate
- Neutralizes concrete that suffers from efflorescence, sweating, and other alkalinity problems
- Helps prevent efflorescence and the leaching of lime
- Removes fine particles and dust that can reduce shine
- Excellent for cleaning concrete after diamond polishing

CUSTOMER SERVICE:

(+32 60 390 752) to verify the most current versions, visit our website: www.convergent-group.com or scan the code.



APPLICATION

BEFORE APPLICATION, ALWAYS DO A SMALL TEST SAMPLE IN A LESS-VISIBLE AREA TO BE SURE THERE ARE NO VARIABLES OR CONTAMINANTS IN THE SUBSTRATE THAT MAY BE INCOMPATIBLE WITH THIS PRODUCT.

- 1. Thoroughly clean the substrate so it is free of all foreign materials such as bond breakers, curing agents, form release oils, dust, construction laitance, drywall residue etc. The surface should be dry before proceeding.
- 2. Use a low-pressure sprayer to apply **Pentra®-Sil (C&N)** so as to saturate the surface.
- 3. Work the **C&N** into the surface using an automatic scrubber or stiff broom to enhance penetration. Allow **Pentra®-Sil (C&N)** to dwell and penetrate 20-30 minutes. Keep the surface moist with **C&N** for 20 to 30 minutes (adding more product if necessary).
- 4. Remove all residual **C&N** with clear water. Let the surface dry.

Make certain the most current versions of **Pentra®-Sil (C&N)** Product Data sheet and MSDS are being used; Please read this information prior to use; call Customer Service (+32 60 390 752) to verify the most current versions or visit our website: www.convergent-group.com. Proper application is the responsibility of the user. Field visits by Convergent Group personnel are for the purpose of making technical recommendations only and not for supervising or providing quality control on the jobsite.

ESTIMATED COVERAGE

Typical Coverage Rates: 1 liter per 6 to 9.8m²

*Coverage rate will vary with concrete quality, finish, and environment

CIFANIIP

Use soap and water to clean tools and equipment. Although **Pentra®-Sil (C&N)** is non-toxic and environmentally safe, it is slightly acidic—use up or dry out extra material and dispose of according to local regulations. Don't pour into sewer systems or storm drains.

HEALTH/SAFETY INFORMATION

Pentra®-Sil (C&N) is an aqueous Lithium solution that uses proprietary compounds. The treatment is mildly acidic and may cause eye and skin irritation.

KEEP OUT OF THE REACH OF CHILDREN. Do not take internally. Avoid prolonged

contact with skin. Avoid ingestion of material. If swallowed, do not induce vomiting– call physician. Avoid contact with eyes. Protective clothing is recommended.

Protective goggles are recommended in case of splashing. If splashed in eyes, wash immediately with clean water and call physician if irritation persists. Contact areas should be thoroughly washed with soap and water. Additional precautions, safety information and first aid treatments are contained in the Material Safety Data Sheet. **Pentra®-Sil (C&N)** will etch glass and painted surfaces. Immediately wash off with water all overspray from glass and painted surfaces. **Caution:** Surfaces wet with **Pentra®-Sil (C&N)** may be slippery.

PROPERTIES

Form: Clear to colorless aqueous solution, slightly acidic

Active Ingredients: 100% of total solids

Specific Gravity: 1.07
Flash Point: N/A
Freeze point: 0°

Coefficient of Friction: Does not change floor friction coefficient*

Depth of Surface Penetration: 2-8mm

Shelf Life: 1 year in factory sealed container

PACKAGING

20 L Basket 200 L Drum 600 L Tote 1000 L Tote

LIMITATIONS

- **Pentra®-Sil (C&N)** is not suitable for asphaltic or non-cementitious surfaces or painted surfaces
- Pentra®-Sil (C&N) will not bridge or fill cracks and will not salvage honey combed or structurally unsound surfaces
- Pentra®-Sil (C&N) is not recommended for plastic concrete or mortar or resinbased terrazzo mixes
- Do not allow **Pentra®-Sil (C&N)** to dry on terrazzo (resin-based) floors except as indicated in application instructions
- Do not allow Pentra®-Sil (C&N) to come in contact with any glass, fabric, metal, or painted surfaces. Immediately wipe contaminated surfaces with a clean water saturated cloth, then wipe dry with a second clean cloth
- For subsequent coatings applications, perform proper surface preparation and consult the coating manufacturer for more instructions

TECHNICAL SERVICE

Customer Care +32 60 390 752

EMAIL

technical@convergent-group.com

WEB

www.convergent-group.com

For chemical/medical emergencies only,

Anti Poison BE +32 70 245 245 Outside USA 352-323-3500

WARRANTY

LIMITED WARRANTY NOTICE. Every reasonable effort is made to apply exacting standards both in the manufacture of our products and in the information that we issue concerning these products and their use. We warrant our products to be of good quality and will replace or, at our election, refund the purchase price of any products proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement or refund, CONVERGENT GROUP S.A. ("CONVERGENT") MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY, RESPECTING ITS PRODUCTS, and CONVERGENT shall have no other liability with respect thereto. Any claim regarding product defect must be received in writing within one (1) year from the date of shipment. No claim will be considered without such written notice or after the specified time interval. User shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith. Any authorized change in the printed recommendations concerning the use of our products must bear the signature of CONVERGENT'S Research Director, This information and all further technical advice are based on CONVERGENT'S present knowledge and experience. However, CONVERGENT assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights. In particular, CONVERGENT disclaims all WARRANTIES, WHETHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. CONVERGENT SHALL NOT BE RESPONSIBLE FOR CONSEQUENTIAL INDIRECT OR INCIDENTAL DAMAGES (INCLUDING LOSS OF PROFITS) OF ANY KIND. CONVERGENT reserves the right to make any changes according to technological progress or further developments. It is the customer's (Authorized Applicator) responsibility and obligation to carefully inspect and test any incoming goods. Performance of the product(s) described herein should be verified by testing and carried out only by qualified experts. It is the sole responsibility of the customer to carry out and arrange for any such testing. Reference to trade names used by other companies is neither a recommendation, nor an endorsement of any product and does not imply that similar products could not be used. CONVERGENT reserves the right to change specifications referred to in this literature at any time, without prior notice. The information contained herein is, to our knowledge, true and accurate. While this material is furnished in good faith, no warranty expressed or implied, of merchantability, completeness, fitness or otherwise is made. This material is offered only for your consideration, investigation and verification, and CONVERGENT disclaims any liability incurred from the use thereof and shall not in any event, be liable for any special, incidental or consequential damages arising from such use. This information is not intended to be all inclusive and the manner and conditions of use and handling of any material may involve other or additional considerations specific to the use or user. Nothing herein should be construed as permission or recommendation to infringe any patent or as to any specific use. No agent, representative or employee of this company is authorized to vary any term of this notice.



Refer to www.convergent-group.com for latest Technical Data Sheet and MSDS.

Convergent Group S.A. - Specialty Chemical Concrete Treatments * ZI de Mariembourg * Rue des Mousquetaires Gris, 35 * 5660 Mariembourg * Belgique (Europe) * +32 60 390 752

UNIQUE STRENGHTS, UNMATCHED PERFORMANCE™

©2020 Convergent Group S.A. All Rights Reserved.

©2020 Convergent Group S.A. All rights reserved.

Pentra®-Sil (C&N) is a registered trademark of Convergent Group S.A. Nano-Lithium® brand name and logo are registered trademarks of Advanced Concrete Technologies, LLC ("ADVAN") and sub-licensed to Convergent Group S.A., under a non exclusive co-brand/technology license. All rights reserved. Products manufactured and marketed by CONVERGENT GROUP S.A. are protected by patents and/or pending patents under license in the United States and other countries by ADVANCED CONCRETE TECHNOLOGIES, LLC. ADVANCED CONCRETE TECHNOLOGIES, LLC makes no claim as to the product performance or product shown to be other than as warranted. REVISION DATEO10220